

OFLE-xx-4A-L

Maßtabelle

du/dt Filter
mit Widerstandsbeschaltung
inkl. Kondensatoren

du/dt Filter 50/60 Hz

Pos.	L in mH	Strom in A	Best.-Num. Fuji	Baugröße	Bild	Verluste ca. W	Isolations- klasse	Anschluß	B	T	H	H mit Klemmen	L1	L3	d1	d2	ca. kg
1	0,263	60	OFLE-30-4A-L	DDUA3545		130	T40F	10	210	125	185	215	175	85	8x12		14
2	0,237	75	OFLE-37-4A-L	DDUA3555		140	T40F	16	210	135	185	245	175	95	8x12		15
3	0,194	91	OFLE-45-4A-L	DDUA3864		190	T40F	KS	230	140	200		180	122	8x12		22
4	0,16	112	OFLE-55-4A-L	DDUA4060		225	T40F	KS	240	201	210		190	125	8x12		25
5	0,122	150	OFLE-75-4A-L	DDUA4080		270	T40F	KS	240	220	210		190	135	8x12		35
6	0,097	176	OFLE-90-4A-L	DDUA4095		300	T40F	KS	240	255	210		190	133	8x12		40
7	0,104	210	OFLE-110-4A-L	DDUTA5090		530	T40F	KS	300	242	260		240	161	11x15		52
8	0,079	253	OFLE-132-4A-L	DDUTA7060		730	T40F	CU30x5	420	217	400		370	144	11x15		65
9	0,068	304	OFLE-160-4A-L	DDUTA7070		680	T40F	CU30x5	420	231	400		370	154	11x15		75
10	0,056	377	OFLE-200-4A-L	DDUTA7080		780	T40F	CU30x5	420	237	400		370	164	11x15		90
11	0,053	415	OFLE-220-4A-L	DDUTA7095		890	T40F	CU30x5	420	245	400		370	179	11x15		100
12	0,039	520	OFLE-280-4A-L	DDUTA70100		835	T40F	CU40x5	420	260	400		370	184	11x15		110
13	0,037	585	OFLE-315-4A-L	DDUTA70100		1050	T40/F	CU40x5	420	280	400		370	184	11x15		115
14	0,033	650	OFLE-355-4A-L	DDUTA70130		1240	T40F	CU50x5	420	310	500		370	214	11x15		170
15	0,029	740	OFLE-400-4A-L	DDUTA70150		1310	T40F	CU50x5	420	330	500		370	234	11x15		195
16	0,026	840	OFLE-450-4A-L	DDUTA70160		1445	T40F	CU60x5	420	340	500		370	244	11x15		210
17	0,024	960	OFLE-500-4A-L	DDUTA70180		1580	T40F	CU70x5	420	360	500		370	264	11x15		240