

Sinusfilter



Pos.	Baugröße BS-Type	Kerngröße	Induk- tivität mH	Nenn- strom A	Maßbild	An- schluß	Isolier- stoff- klasse	B	T	T1	H	L1	L3	d1	d2	Erdung	Ca. kg
1	OFLE-3,5A-4	DDUA 2021	16	3,5	S1	KL	T 40/F	125	65	110	180	100	45	5x8	2,5	AMP-Erdung	2,6
2	OFLE-4,5A-4	DDUA 2031	11	4,5	S1	KL	T 40/F	125	75	110	180	100	55	5x8	2,5	AMP-Erdung	3,0
3	OFLE-8A-4	DDUA 2541	7,2	8,0	S1	KL	T 40/F	155	95	118	205	130	70	8x12	4,0	M 5	6,6
4	OFLE-13A-4	DDUA 3031	4,2	13	S1	KL	T 40/F	190	100	125	230	170	58	8x12	4,0	M 6	7,3
5	OFLE-18A-4	DDUA 3051	3,5	18	S1	KL	T 40/F	190	120	125	230	170	78	8x12	10,0	M 6	11,5
6	OFLE-24A-4	DDUA 3545	2,4	24	S1	KL	T 40/F	210	125	135	260	175	85	8x12	10,0	M 6	14,0
7	OFLE-32A-4	DDUA 3555	2,0	32	S1	KL	T 40/F	210	135	135	260	175	95	8x12	10,0	M 6	16,0
8	OFLE-48A-4	DDUA 4070	1,5	48	S2	KL	T 40/F	240	210	< T	290	190	125	8x12	10,0	M 8	28,0
9	OFLE-60A-4	DDUTA 4080	1,1	60	S2	KL	T 40/F	240	220	< T	290	190	135	8x12	16,0	M 8	35,0
10	OFLE-75A-4	DDUTA 5058	0,9	75	S2	KL	T 40/F	300	210	< T	345	240	134	11x15	35,0	M 8	42,0
11	OFLE-90A-4	DDUTA 5063	0,8	90	S2	KL	T 40/F	300	215	< T	345	240	139	11x15	35,0	M 8	46,0
12	OFLE-110A-4	DDUTA 5085	0,7	110	S2	KL	T 40/F	300	237	< T	345	240	161	11x15	50,0	M 8	58,0
13	OFLE-150A-4	DDUTA 7060	0,5	150	S2	KL	T 40/F	420	217	< T	470	370	142	11x15	50,0	M 10	75,0
14	OFLE-180A-4	DDUTA 7075	0,4	180	S3	S	T 40/F	420	235	< T	470	370	157	11x15	11,0	M 10	88,0
15	OFLE-210A-4	DDUTA 70100	0,4	210	S3	S	T 40/F	420	260	< T	470	370	182	11x15	11,0	M 10	115,0
16	OFLE-270A-4	DDUTA 70135	0,3	270	S3	S	T 40/F	420	295	< T	470	370	217	11x15	11,0	M 10	150,0
17	OFLE-325A-4	DDUTA 70130	0,3	325	S3	S	T 40/F	480	310	< T	580	430	234	13x15	11,0	M 10	194,0
18	OFLE-410A-4	DDUTA 70130	0,2	410	S3	S	T 40/F	480	310	< T	580	430	234	13x15	11,0	M 10	206,0

Alle Maße sind ca. Maße in mm. Technische Änderungen vorbehalten.

KL = Klemme KS = Kabelschuhe S = Schiene