

Модель	Номинальная мощность подключаемого э/д, кВт	Номинальный ток, А (3 фазы / 380 В)	Перегрузка, % в теч. мин.	Размеры (Ш x В x Г), мм	Время торможения, с
ADV 1.50 M420-M	1.5/0.75	3.8/2.1	130/150	148x223x159	0-3000
ADV 2.20 M420-M	2.2/1.5	5.1/3.8	130/150	148x223x159	0-3000
ADV 4.00 M420-M	4/2.2	9/5.1	130/150	148x223x159	0-3000
ADV 5.50 M420-M	5.5/4	13/9	130/150	148x223x159	0-3000
ADV 7.50 M420-M	7.5/5.5	17/13	130/150	162x238x165	0-3000
ADV 11.0 M420-M	11/7.5	25/20	130/150	222x340x194	0-3000
ADV 15.0 M420-M	15/11	32/25	130/150	222x340x194	0-3000
ADV 18.5 M420-M	18.5/15	37/32	130/150	222x340x194	0-3000
ADV 22.0 M420-M	22/18.5	45/37	130/150	260x485x230	0-3000
ADV 30.0 M420-M	30/22	60/45	130/150	260x485x230	0-3000
ADV 37.0 M420-M	37/30	75/60	130/150	260x485x230	0-3000
ADV 45.0 M420-M	45/37	90/75	130/150	330x565x252	0-3000
ADV 55.0 M420-M	55/45	110/90	130/150	330x565x252	0-3000
ADV 75.0 M420-M	75/55	152/110	130/150	380x588x266	0-3000
ADV 90.0 M420-M	90/75	176/152	130/150	460x660x290	0-3000
ADV 110 M420-M	110/90	210/176	130/150	460x660x290	0-3000
ADV 132 M420-M	132/110	253/210	130/150	475x875x305	0-3000
ADV 160 M420-M	160/132	304/253	130/150	475x875x305	0-3000
ADV 185 M420-M	185/160	340/304	130/150	520x1100x355	0-3000
ADV 200 M420-M	200/185	380/340	130/150	520x1100x355	0-3000
ADV 220 M420-M	220/200	426/380	130/150	700x1360x380	0-3000
ADV 250 M420-M	250/220	465/426	130/150	700x1360x380	0-3000
ADV 280 M420-M	280/250	520/465	130/150	700x1360x380	0-3000
ADV 315 M420-M	315/280	585/520	130/150	700x1360x380	0-3000
ADV 355 M420-M	355/315	650/585	130/150	900x1350x455	0-3000
ADV 400 M420-M	400/355	725/650	130/150	900x1350x455	0-3000
ADV 450 M420-M	450/400	820/725	130/150	900x1350x455	0-3000