

Модель	Номинальная мощность подключаемого э/д, кВт	Номинальный ток, А (3 фазы / 380~480 В)	Перегрузка, % в теч. мин.	Размеры (Ш x В x Г), мм	Масса, кг
FRN0.75F1S-4E	0,75	2,5	120	150x260x163	3,1
FRN1.5F1S-4E	1,5	3,7	120	150x260x145	3,2
FRN2.2F1S-4E	2,2	5,5	120	150x260x163	3,3
FRN4.0F1S-4E	4,0	9,0	120	150x260x163	3,4
FRN5.5F1S-4E	5,5	12,5	120	150x260x163	3,4
FRN7.5F1S-4E	7,5	16,5	120	220x260x215	5,8
FRN11F1S-4E	11	23	120	220x260x215	6,0
FRN15F1S-4E	15	30	120	220x260x215	6,9
FRN18.5F1S-4E	18,5	37	120	250x400x215	9,4
FRN22F1S-4E	22	44	120	250x400x215	9,9
FRN30F1S-4E	30	59	120	250x400x215	11,5
FRN37F1S-4E	37	72	120	320x550x255	23
FRN45F1S-4E	45	85	120	320x550x255	24
FRN55F1S-4E	55	105	120	355x550x270	33
FRN75F1S-4E	75	139	120	355x615x270	34
FRN90F1S-4E	90	168	120	355x740x300	42
FRN110F1S-4E	110	203	120	355x740x300	45
FRN132F1S-4E	132	240	120	530x740x315	63
FRN160F1S-4E	160	290	120	530x740x315	67
FRN200F1S-4E	200	360	120	530x740x360	96
FRN220F1S-4E	220	415	120	530x1000x360	98
FRN280F1S-4E	280	520	120	530x1000x360	162
FRN315F1S-4E	315	585	120	680x1000x380	165
FRN355F1S-4E	355	650	120	680x1000x380	282
FRN400F1S-4E	400	740	120	680x1400x440	286
FRN450F1S-4E	450	840	120	680x1400x440	355
FRN500F1S-4E	500	960	120	880x1400x440	360
FRN560F1S-4E	560			880x1400x440	360